

## IN THE CLAIMS

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

**Claim 1 (Original):** A method for controlling power to a subscriber identity module (SIM) in a wireless communication device (WCD), the method comprising:

supplying power to the SIM when a request is pending for service by the SIM;

supplying power to the SIM when a software module running on the WCD requests maintenance of power to the SIM; and

terminating power to the SIM when no request is pending for service by the SIM and no software module running on the WCD requests maintenance of power to the SIM.

**Claim 2 (Original):** The method of claim 1, further comprising re-initiating supply of power to the SIM following termination of power to the SIM when a request from the WCD is pending for service by the SIM.

**Claim 3 (Original):** The method of claim 1, further comprising determining whether a request from the WCD is pending for service by the SIM by inspecting a request queue associated with the SIM.

**Claim 4 (Original):** The method of claim 1, further comprising re-initiating supply of power to the SIM when a software module running on the WCD requests supply of power to the SIM.

**Claim 5 (Original):** The method of claim 4, further comprising determining whether a software module running on the WCD requests supply of power to the SIM by polling any of a plurality of software modules running on the WCD.

Claim 6 (Original): The method of claim 4, further comprising:  
asserting respective bits in a data structure when corresponding software modules ~~asserting~~  
on the WCD request supply of power to the SIM;  
determining whether a software module running on the WCD requests supply of power to  
the SIM by analyzing the data structure; and  
when any of the bits in the data structure is asserted, supplying power to the SIM.

Claim 7 (Original): The method of claim 1, wherein supplying power to the SIM includes  
maintaining power to the SIM.

Claim 8 (Original): The method of claim 1, wherein the SIM includes an interface circuit that  
interfaces with the WCD, and terminating power to the SIM includes terminating power to the  
interface circuit.

Claim 9 (Original): The method of claim 1, wherein the SIM includes a power supply line  
coupled to the WCD, and terminating power to the SIM includes terminating power to the power  
supply line.

Claim 10 (Original): The method of claim 1, wherein the SIM includes an interface circuit that  
interfaces with the WCD, the interface circuit including a clock input to the removable user  
identity module, and wherein terminating power to the SIM includes terminating power after  
terminating a clock signal to the clock input.

Claim 11 (Currently amended): The method of claim 1, further comprising:  
storing a user access code associated with the SIM in a memory associated with the  
WCD;  
retrieving the user access code from the memory when power is supplied to the SIM  
following the termination of power to the SIM; and  
using the retrieved user access code in a security authorization process in the WCD to  
authorize use of secure features of the SIM.

Claim 12 (Original): The method of claim 11, wherein storing the user access code includes storing the user access code upon the termination of power to the SIM.

Claim 13 (Original): The method of claim 11, wherein the SIM is one of a removable user identification module (R-UIM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

Claim 14 (Original): The method of claim 11, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

Claim 15 (Original): The method of claim 1, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

Claim 16 (Original): The method of claim 1, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

Claim 17 (Original): A system for controlling power to a removable user identity module (SIM) in a wireless communication device (WCD), the system comprising:

a power source coupled to the SIM; and

a processor that controls the power source to:

- (a) supply power from the power source to the SIM when a request from the WCD is pending for service by the SIM,
- (b) supply power from the power source to the SIM when a software module running on the WCD requests maintenance of power to the SIM, and
- (c) terminate power to the SIM when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM.

Claim 18 (Original): The system of claim 17, wherein the processor controls the power source to re-initiate supply of power to the SIM following termination of power to the SIM when a request from the WCD is pending for service by the SIM.

Claim 19 (Original): The system of claim 17, wherein the processor determines whether a request from the WCD is pending for service by the SIM by inspecting a request queue associated with the SIM.

Claim 20 (Original): The system of claim 17, wherein the processor controls the power source to re-initiate supply of power to the SIM when a software module running on the WCD requests supply of power to the SIM.

Claim 21 (Original): The system of claim 20, wherein the processor determines whether a software module running on the WCD requests supply of power to the SIM by polling any of a plurality of software modules running on the WCD.

Claim 22 (Original): The system of claim 20, further comprising a memory storing a data structure with bits corresponding to software modules running on the WCD, wherein the processor asserts respective bits in the data structure when corresponding software modules running on the WCD request supply of power to the SIM, determines whether a software module running on the WCD requests supply of power to the SIM by analyzing the data structure, and, when any of the bits in the data structure is asserted, controls the power source to supply power to the SIM.

Claim 23 (Original): The system of claim 17, wherein the processor controls the power source to maintain power to the SIM.

Claim 24 (Original): The system of claim 17, wherein the SIM includes an interface circuit that interfaces with the WCD, and the processor controls the power source to terminate power to the SIM by terminating power to the interface circuit.

Claim 25 (Original): The system of claim 17, wherein the SIM includes a power supply line coupled to the WCD, and the processor controls the power source to terminate power to the SIM by terminating power to the power supply line.

Claim 26 (Original): The system of claim 17, wherein the SIM includes an interface circuit that interfaces with the WCD, the interface circuit including a clock input to the removable user identity module, and wherein the processor controls the power source to terminate power to the SIM by terminating power after terminating a clock signal to the clock input.

Claim 27 (Currently amended): The system of claim 17, further comprising a memory associated with the WCD that stores a user access code associated with the SIM, wherein the processor retrieves the user access code from the memory when power is supplied to the SIM following the termination of power to the SIM, and uses the retrieved user access code in a security authorization process in the WCD to authorize use of the secure features SIM.

Claim 28 (Original): The system of claim 27, wherein the processor stores the user access code upon the termination of power to the SIM.

Claim 29 (Original): The system of claim 27, wherein the SIM is one of a removable user identification module (R-UIM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

Claim 30 (Original): The system of claim 27, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

Claim 31 (Original): The system of claim 17, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

**Claim 32 (Original):** The system of claim 17, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

**Claim 33 (Original):** A computer-readable medium containing instructions that cause a programmable processor to: supply power to a removable user identity module (SIM) when a request from a wireless communication device (WCD) is pending for service by the SIM;

supply power to the SIM when a software module running on the WCD requests maintenance of power to the SIM; and

terminate power to the SIM when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM.

**Claim 34 (Original):** The computer-readable medium of claim 33, wherein the instructions cause the processor to re-initiate supply of power to the SIM following termination of power to the SIM when a request from the WCD is pending for service by the SIM.

**Claim 35 (Original):** The computer-readable medium of claim 33, wherein the instructions cause the processor to determine whether a request from the WCD is pending for service by the SIM by inspecting a request queue associated with the SIM.

**Claim 36 (Original):** The computer-readable medium of claim 33, wherein the instructions cause the processor to re-initiate supply of power to the SIM when a software module running on the WCD requests supply of power to the SIM.

**Claim 37 (Original):** The computer-readable medium of claim 36, wherein the instructions cause the processor to determine whether a software module running on the WCD requests supply of power to the SIM by polling any of a plurality of software modules running on the WCD.

**Claim 38 (Original):** The computer-readable medium of claim 36, wherein the instructions cause the processor to:

define a data structure with bits corresponding to software modules running on the WCD;

assert respective bits in the data structure when corresponding software modules running on the WCD request supply of power to the SIM;

determine whether a software module running on the WCD requests supply of power to the SIM by analyzing the data structure; and

when any of the bits in the data structure is asserted, supply power to the SIM.

**Claim 39 (Original):** The computer-readable medium of claim 37, wherein the instructions cause the processor to supply power to the SIM by maintaining power to the SIM.

**Claim 40 (Original):** The computer-readable medium of claim 33, wherein the SIM includes an interface circuit that interfaces with the WCD, and the instructions cause the processor to terminate power to the SIM by terminating power to the interface circuit.

**Claim 41 (Original):** The computer-readable medium of claim 33, wherein the SIM includes a power supply line coupled to the WCD, and the instructions cause the processor to terminate power to the SIM by terminating power to the power supply line.

**Claim 42 (Original):** The computer-readable medium of claim 33, wherein the SIM includes an interface circuit that interfaces with the WCD, the interface circuit including a clock input to the removable user identity module, and the instructions cause the processor to terminate power to the SIM by terminating power after terminating a clock signal to the clock input.

**Claim 43 (Currently amended):** The computer-readable medium of claim 33, wherein the instructions cause the processor to:

store a user access code associated with the SIM in a memory associated with the WCD;

retrieve the user access code from the memory when power is supplied to the SIM following the termination of power to the SIM; and

use the retrieved user access code in a security authorization process in the WCD to authorize use of the WCD.

Claim 44 (Original): The computer-readable medium of claim 43, wherein the instructions cause the processor to store the user access code upon the termination of power to the SIM.

Claim 45 (Original): The computer-readable medium of claim 43, wherein the SIM is one of a removable user identification module (R-UIM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

Claim 46 (Original): The computer-readable medium of claim 43, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

Claim 47 (Original): The computer-readable medium of claim 33, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

Claim 48 (Original): The computer-readable medium of claim 33, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

Claim 49 (Currently amended): A method comprising:  
storing a user access code associated with a subscriber identity module (SIM) in a memory associated with a wireless communication device (WCD);  
retrieving the user access code from the memory when power is resupplied to the SIM;  
and  
using the retrieved user access code in a security authorization process in the WCD to authorize use of secure features of the SIM.

Claim 50 (Original): The method of claim 49, further comprising:



terminating power to the SIM when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM; and terminating power to the SIM when power to the WCD is terminated.

**Claim 51 (Original):** The method of claim 50, further comprising:

retrieving and using the user access code when power is resupplied to the SIM following termination when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM; and

accepting and using user input as the user access code when power is resupplied to the SIM following termination when power to the WCD is terminated.

**Claim 52 (Original):** The method of claim 49, wherein storing the user access code includes storing the user access code when power to the SIM is terminated.

**Claim 53 (Original):** The method of claim 49, wherein the SIM is one of a removable user identification module (R-UIM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

**Claim 54 (Original):** The method of claim 49, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

**Claim 55 (Original):** The method of claim 49, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

**Claim 56 (Original):** The method of claim 49, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

**Claim 57 (Currently amended):** A system comprising:

a memory that stores a user access code associated with a removable user identity module (SIM) in a memory associated with a wireless communication device (WCD); and

a processor that retrieves the user access code from the memory when power is resupplied to the SIM, and uses the retrieved user access code in a security authorization process in the WCD to authorize use of the WCD.

Claim 58 (Original): The system of claim 57, wherein the processor terminates power to the SIM when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM, and terminates power to the SIM when power to the WCD is terminated.

Claim 59 (Original): The system of claim 57, wherein the processor retrieves and uses the user access code when power is resupplied to the SIM following termination when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM, and accepts and uses user input as the user access code when power is resupplied to the SIM following termination when power to the WCD is terminated.

Claim 60 (Original): The system of claim 57, wherein the processor stores the user access code in the memory when power to the SIM is terminated.

Claim 61 (Original): The system of claim 57, wherein the SIM is one of a removable user identification module (R-UM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

Claim 62 (Original): The system of claim 57, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

Claim 63 (Original): The system of claim 57, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

Claim 64 (Original): The system of claim 57, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

Claim 65 (Currently amended): A computer-readable medium containing instructions that cause a processor to:

store a user access code associated with a SIM in a memory associated with a wireless communication device (WCD);

retrieve the user access code from the memory when power is resupplied to the SIM; and

use the retrieved user access code in a security authorization process in the WCD to authorize use of the WCD.

Claim 66 (Original): The computer-readable medium of claim 65, wherein the instructions cause the processor to:

terminate power to the SIM when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM; and

terminate power to the SIM when power to the WCD is terminated.

Claim 67 (Original): The computer-readable medium of claim 65, wherein the instructions cause the processor to:

retrieve and use the user access code when power is resupplied to the SIM following termination when no request from the WCD is pending for service by the SIM and no software module running on the WCD requests supply of power to the SIM; and

accept and use user input as the user access code when power is resupplied to the SIM following termination when power to the WCD is terminated.

Claim 68 (Original): The computer-readable medium of claim 65, wherein the instructions cause the processor to store the user access code when power to the SIM is terminated.

Claim 69 (Original): The computer-readable medium of claim 65, wherein the SIM is one of a removable user identification module (R-UIM) and a GSM SIM, and the user access code is a card holder verification (CHV) code.

Claim 70 (Original): The computer-readable medium of claim 65, wherein the SIM is a universal subscriber identification module (USIM), and the user access code is a personal identification number (PIN).

Claim 71 (Original): The computer-readable medium of claim 65, wherein the SIM is one of a removable user identification module (R-UIM), a GSM SIM, and a universal subscriber identification module (USIM).

Claim 72 (Original): The computer-readable medium of claim 65, wherein the WCD is one of a cellular radiotelephone, a satellite radiotelephone, a PCMCIA card, and a PDA that communicates according to one of the CDMA standard, the GSM standard, and the WCDMA standard.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**